



Platinum Tyre Changer & Wheel Balancer Package

The Platinum Tyre Changer includes the following as standard:

- 2x Plastic inserts for fitting head.
- 4x Plastic Jaw protection covers.
- 1x Plastic bead breaker.
- 1x Tyre lever bar.
- 1x Air inflation gun.
- 1x Filter lubrication regulator.
- 1x Soap reservoir.

Tyre Changer Features:

- Large 28" turn table
- Hand bead breaker controller
- Aluminium bead breaker cylinder with 2500KG pressure.
- Chromium alloy assembling head.
- Zinc-base alloy gear box.
- LCD digital inflator,
- High-pressure explosion-proof air-oil separator.
- Aluminium five way valve, swing air valve.

	<i>Tyre Changer Spec</i>
Rim material	Steel or Alloy
Max. wheel width	14"
Inter clamping	15"-28"
Outer clamping	14"-26"
Power supply	110V/220V/380V 1Ph/3Ph 50/60Hz
Air supply	8-10Bar
Motor power	0.75Kw-1.1Kw
Noise level	75dB

The Platinum Wheel Balancer comes with the following features as standard:

- Suitable For Luxury Vehicle, SUV, BPV, Light Truck.
- Extend Balance Shaft, Long Measure Ruler.
- Adapt Auto Self-accurate And Auto Self-diagnosis.
- Auto A,D Data Input.
- High Precise Long Shaft For Flat Tire.
- With Static Balance And Dynamic Balance Mode.
- Optional Wheel Cover, Universal Cones And Larger Cones.

	<i>Wheel Balancer Spec</i>
Data Input	Semi Automatic
Calibration	Self-calibration
Max. wheel weight	65Kg/143 lb
Max. tyre diameter	47"
Rim diameter	10" – 24"
Rim width	5" – 14"
Power supply	1PH 240V 50Hz
Measuring time	6-8s
Noise level	65dB

